

Adhesion	JIS K5600-4-6	Cross cut method	Classification 0
Alkali resistant (ph13)	JIS K5600-6-2	Sodium hydroxide 5% (NaOH)	---
Acid resistant (ph4)	JIS K5600-6-2	Sulfuric acid 5% (H2S04)	---
Water resistance	JIS K5600-6-2	Sulfuric acid 5% (H2S04)	----

Coating Specification:

<u>Product name</u>	<u>Packing</u>	<u>Area Coverage</u>	<u>Coating m²/1 metal can</u>
E-COOL Each Color	18Kgs/can	0.4Kg/m ²	50m ²
E-COOL NON-SKID Each Color	18Kgs/can	1.0Kg/m ²	16m ²

Painting Tools


Uses

Roller, Brush Galvanized metal, Slate for factory · warehouse, Steel,
 -ditto - Gymnasium Roof, Plant, Cattle, Garage, Waterproof Rubber sheet,
 Others:

E-COOL COLOR


White

白




Light Gray

淡灰



Dark Gray

濃灰



Blue 1

青1




Blue 2

青2



Brown 1

茶1



Brown 2

茶2



Green

緑



Yellow soil

黄土




Beige

ベージュ



Waterproof Rubber Protection

防水ゴム保護用



- Light Color Available : Excluding White, Light Gray, Dark Gray, Water Proof Rubber protection.
- Special color makes accordingly.
- Color may appear difference on screen than actual product.